

**SIN CHEW ALARM PTE LTD**

Co. Reg. No: 199003973E
 GST Reg. No: M2-0094814-9
 E-mail: enquiry@sinchewalarm.com
 http://www.sinchewalarm.com



SINGAPORE
 ENTERPRISE
 AWARDS 2015



No. 10 Upper Aljunied Link #06-02/03/04, Singapore 367904 Tel: (65) 6287 2788 Fax: (65) 6287 0856

3MP Bullet IR60 VR IP Camera

SCALIN60S200



Model NO.	SCALIN60S200
CAMERA	
Image Sensor	IMX323
Main processor	HI3516CV200
Resolution	1080P
Effective Pixels	1985(H)*1105(V)
Compression	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Manual
Pixels	3MP
NIGHT VISION	
Infrared LED	42 x 4PCS
Infrared Distance	60M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
NETWORK	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Video Delay	0.3S (Within the Lan)

Model NO.	SCALIN60S200
Main Stream 1	1920*1080@25fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	720*480@25fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@25fps
IE Browser	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
CAMERA FEATURES	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	/
Defog Mode	Support
ROI	Support
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands
GENERAL	
Housing	Metal , IP66
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	275(W) x 91(H) x 80(D)mm
Weight	1400g

*Due to product enhancement, Sin Chew Alarm reserved the right to change/modify specifications without prior notice.