


CABLE LUGS



Material : 99.9 percent copper tube T2 coated with tin

Item	Part No.	A (mm)	C (mm)	F (mm)	D (mm)	E (mm)	J (mm)	G (mm)
1	SC 4-6	3.1	4.8	1.7	10.2	6.2	20.5	5.0
2	SC 4-8	3.1	4.8	1.7	10.2	8.2	20.5	5.0
3	SC 6-6	3.8	5.5	1.7	9.0	6.2	24.0	6.0
4	SC 6-8	3.8	5.5	1.7	9.0	8.2	24.0	6.0
5	SC 10-6	4.8	6.8	2.0	9.8	6.2	25.5	6.0
6	SC 10-8	4.8	6.8	2.0	12	8.2	25.5	6.0
7	SC 10-10	4.8	6.8	2.0	14.5	10.5	28.0	6.0
8	SC 16-6	5.5	7.5	2.0	12.0	6.2	30.0	7.0
9	SC 16-8	5.5	7.5	2.0	12.0	8.2	30.0	7.0
10	SC 16-10	5.5	7.5	2.0	15.0	10.5	30.0	7.5
11	SC 25-6	7.0	9.0	2.0	13.1	6.2	33.0	8.0
12	SC 25-8	7.0	9.0	2.0	13.1	8.2	33.0	8.0
13	SC 25-10	7.0	9.0	2.0	14.5	10.5	33.0	8.0
14	SC 35-6	8.3	10.5	2.2	15.3	6.2	38.0	9.0
15	SC 35-8	8.3	10.5	2.2	15.3	8.2	38.0	9.0
16	SC 35-10	8.3	10.5	2.2	15.3	8.2	38.0	9.0
17	SC 35-12	8.3	10.5	2.2	16.5	12.5	38.0	9.0
18	SC 50-6	9.8	12.5	2.7	18.6	6.2	45.0	10.0
19	SC 50-8	9.8	12.5	2.7	18.6	8.2	45.0	10.0
20	SC 50-10	9.8	12.5	2.7	18.6	10.5	45.0	10.0
21	SC 50-12	9.8	12.5	2.7	18.6	12.5	45.0	10.0
22	SC 70-6	11.5	14.5	3.0	20.9	6.2	49.0	12.0
23	SC 70-8	11.5	14.5	3.0	20.9	8.2	49.0	12.0
24	SC 70-10	11.5	14.5	3.0	20.9	10.5	49.0	12.0
25	SC 70-12	11.5	14.5	3.0	20.9	12.5	49.0	12.0
26	SC 95-6	13.8	17.5	3.7	24.8	6.2	54.0	13.0
27	SC 95-8	13.8	17.5	3.7	24.8	8.2	54.0	13.0
28	SC 95-10	13.8	17.5	3.7	24.8	10.5	54.0	13.0
29	SC 95-12	13.8	17.5	3.7	24.8	12.5	54.0	13.0
29	SC 95-16	13.8	17.5	3.7	24.8	16.5	54.0	13.0
30	SC 120-6	15.5	19.5	4.0	28.3	6.2	62.0	15.0
31	SC 120-8	15.5	19.5	4.0	28.3	8.2	62.0	15.0
32	SC 120-10	15.5	19.5	4.0	28.3	10.5	62.0	15.0
33	SC 120-12	15.5	19.5	4.0	28.3	12.5	62.0	15.0
34	SC 120-16	15.5	19.5	4.0	28.3	16.5	62.0	15.0
35	SC 150-8	16.5	21.0	4.5	29.6	8.2	68.0	16.0
36	SC 150-10	16.5	21.0	4.5	29.6	10.5	68.0	16.0
37	SC 150-12	16.5	21.0	4.5	29.6	12.5	68.0	16.0
38	SC 150-16	16.5	21.0	4.5	29.6	16.5	68.0	16.0
39	SC 185-10	18.8	23.5	4.7	34.0	10.5	76.0	17.5
40	SC 185-12	18.8	23.5	4.7	34.0	12.5	76.0	17.5
41	SC 185-16	18.8	23.5	4.7	34.0	16.5	76.0	17.5
40	SC 240-10	21.0	26.0	5.0	38.0	10.5	90.0	20.0
41	SC 240-12	21.0	26.0	5.0	38.0	12.5	90.0	20.0
42	SC 240-16	21.0	26.0	5.0	38.0	16.5	90.0	20.0
43	SC 300-12	23.5	30.0	6.5	43.0	12.5	98.0	22.0
44	SC 300-16	23.5	30.0	6.5	43.0	16.5	98.0	22.0
45	SC 300-20	23.5	30.0	6.5	43.0	20.5	98.0	22.0
46	SC 400-12	28.5	36.5	8.0	50.0	12.5	110.0	26.0
47	SC 400-16	28.5	36.5	8.0	50.0	16.5	110.0	26.0
48	SC 400-20	28.5	36.5	8.0	50.0	20.5	110.0	26.0
49	SC 500-12	30.0	39.0	9.0	56.0	12.5	120.0	28.0
50	SC 500-16	30.0	39.0	9.0	56.0	16.5	120.0	28.0
51	SC 500-20	30.0	39.0	9.0	56.0	20.5	120.0	28.0
52	SC 630-12	35.0	45.0	10.0	65.0	12.5	140.0	33.0
53	SC630-16	35.0	45.0	10.0	65.0	16.5	140.0	33.0
54	SC 630-20	35.0	45.0	10.0	65.0	20.5	140.0	33.0